

ELEKTRİKLİ HIZ KAFASI

- Elektrikli Hız Kafası
- Sınıfın en güçlüsü 500 W
- 60,000 dev. / dak.



 **ALLORDER**® 

WT80.120K-12HYM

Technical Specifications:

➤ Ceramic hybrid ball bearing (pcs):	2
➤ Lifetime lubricated:	Oil Jet
➤ Rated power	1.3 kW
➤ Voltage:	220 V
➤ Current:	6 A
➤ Frequency:	2,000 Hz
➤ Motor poles:	2
➤ Rated rotation speed:	120,000 rpm
➤ Motor protection:	PTC
➤ Housing diameter:	80 mm
➤ Cooling system:	Liquid cooled,water
➤ Cooling system:	Liquid cooled,water
➤ Sealing air:	Yes
➤ Tool change:	Manual
➤ Clamping change up to:	6 mm
➤ Tool holder:	WTD10
➤ Weight:	4.5 kg
➤ Inner taper run out:	< 2 µ m

WTBT4.60K-12HYM

Technical Specifications:

➤ Ceramic hybrid ball bearing (pcs):	2
➤ Lifetime lubricated:	maintenance free
➤ Rated power	500 W
➤ Voltage:	150 V
➤ Current:	3.5 A
➤ Frequency:	1,000 Hz
➤ Motor poles:	2
➤ Rated rotation speed:	60,000 rpm
➤ Motor protection:	PTC
➤ Housing diameter:	Bt40 Interface
➤ Cooling system:	Air cooled
➤ Cooling system:	Air cooled
➤ Sealing air:	Yes
➤ Tool change:	Manual
➤ Clamping change up to:	6 mm
➤ Tool holder:	WTD10
➤ Weight:	2.5 kg
➤ Inner taper run out:	< 2 µ m

WTEC-01 Control Unit

Technical Specifications:

➤ Motor Speed	1000~120,000 rpm
➤ Power Source	AC 30Ø220V
➤ Max. power	2,2 kW
➤ Power Consumption	11 A
➤ Air Input	1~10 kgf/cm ²
➤ Air Output	1~ 6 kgf/cm ²
➤ Weight	12.5 kg
➤ Accessories	
• Motor Cord	1.5 M
• Air Hose with Filter	
• Air Hose with Filter and Lubricator (option)	